Quicksocrete HP

constructive solutions

Set accelerating concrete / mortar

Description

A concentrated liquid for addition to concrete and mortar mixes for accelerating the setting time and hardening of concrete and mortar, sealing leakages and plugging of water through the concrete.

Advantages

- Fast setting
- · Good bonding to the concrete
- Rapid strength gain and high ultimate strength
- Easy to apply

Properties

Appearance : Clear liquid
Specific gravity : 1.30 kg / ltr
Active content : 25 –30 %

Technical Support

Fosroc provides a technical advisory for on-site assistance and advice on admixture selection, evaluation trials and dispensing equipment; Technical data and guidance can be provided for admixtures and other products for use with fresh and hardened concrete.

Specification Clauses

Quicksocrete complies with standard ASTM C-494: 92 Type C as accelerating admixture.

Application Instruction

Surface Preparation

Clean surface to be repaired or plugged from dirt, oil or contaminant materials.

Mixing

Prepared cement or mortar in the conveniencemixing bowl, add Quicksocrete at recommended quantity (see the dosage) to the mixing bowl. For small quantity mixing by hand is sufficient.

Dosage

Typical dosage is 25 – 35% to cement weight. Exact dosage should be obtained from trial.

Packaging

Quicksocrete is supplied in 20-litre pail and 5-litre jerican.

Storage

Quicksocrete has a minimum shelf life of 12 months provide the temperature is kept within the range of 2° C to 50° C.

Precautions

Health and Safety

Quicksocrete is slightly toxic and must not be ingested. It is alkaline and prolonged contact with the skin must be avoided, splashes to the skin should be removed with water. In the event of splashes to the eyes should be washed immediately with plenty of water and seek medical advice.

Additional Information

Technical data and guidance can be provided on a wide range admixtures and concreting aids including accelerators, plasticizers, air entraining agents, waterproofers, mould release agents, surface retarders, workability aids and repair materials.

Quicksocrete HP

PT.FOSROC

Indonesia

JI.Akasia II Blok A8 No.1 Delta Silicon Industrial Park Lippo Cikarang Bekasi 17550 Indonesia

www.fosroc.com

telephone: +62 21 897 2103 +62 22 520 1308 +62 31 502 9142 fax: +62 21 897 2107 +62 22 522 2713 +62 31 502 2711 email:

indonesia@fosroc.co.id